


**MVP PLUS****WIDE-OUT**

WESTERN PRODUCTS
P.O. BOX 245038
MILWAUKEE, WI 53224-9538
www.westernplows.com




A DIVISION OF DOUGLAS DYNAMICS, L.L.C.

96400 WIDE-OUT™
96700 MVP PLUS™
and 96369 MVP®
JOYSTICK CONTROLS
Installation Instructions



WIDE-OUT



MVP PLUS & MVP

⚠ CAUTION

Read this document before installing the snowplow.

⚠ CAUTION

See your WESTERN® outlet for specific application recommendations before installation. The Selection List has specific vehicle and snowplow requirements.

SAFETY DEFINITIONS

⚠ WARNING

Indicates a potentially hazardous situation that, if not avoided, could result in death or serious personal injury.

⚠ CAUTION

Indicates a potentially hazardous situation that, if not avoided, may result in minor or moderate injury. It may also be used to alert against unsafe practices.

NOTE: Indicates a situation or action that can lead to damage to your snowplow and vehicle or other property. Other useful information can also be described.

FUSES

The WESTERN electrical and hydraulic systems contain several automotive blade-style fuses. If a problem should occur and fuse replacement is necessary, the replacement fuse must be of the same type and amperage rating as the original. Installing a fuse with a higher rating could damage the system and could start a fire. Fuse Replacement, including fuse ratings and locations, is located in the Maintenance Section of the Owner's Manual.


NOTE: The MVP PLUS & WIDE-OUT controls (4-pin square connector) do not contain on-board fuses. Consult your snowplow Owner's Manual for fuse replacement. Fuses are located both under hood and on the hydraulic unit.

MVP JOYSTICK CONTROL (10-pin round connector) ON-BOARD FUSES

NOTE: Circuit board may be damaged by static electricity. Always touch ground before handling PC board.

This control contains two 5AFB printed circuit (PC) board mounted fuses. If the control does not function and the under hood 10-amp in-line fuse is not blown, one or both of these 5AFB PC board-mounted fuses may be blown. They can be removed by pulling them out of the PC board holders with small needle-nose pliers. They should be replaced with 5AFB SMD fuses.


When service is necessary, your local WESTERN® outlet knows your snowplow best. Contact your snowplow outlet for maintenance, service or any other assistance you may require.



INSTALLING DASH BRACKET

⚠ CAUTION

Before drilling holes, check to be sure that no vehicle wiring or other components could be damaged.



Metal Dash Only:

1. Using two of the four clearance holes on narrow end of the bracket as guides, drill two 9/32" holes in dash.
2. Attach control to control bracket with two #8 x 5/8" self-tapping screws, or with the PRO-GRIP Mount Kit (PN 49305K) as instructed.
3. Attach bracket to dash with two 1/4" x 3/4" cap screws, 1/4" lock washers and 1/4" nuts.

Plastic Dash Only:

1. Using the four clearance holes on the narrow end of the bracket as guides, drill four 9/64" tap holes in dash.
2. Attach bracket to dash with four #12 x 3/4" self-tapping screws.


PRO-GRIP MOUNT KIT

The PRO-GRIP Mount Kit will secure your WESTERN® joystick control to interior vehicle cab surfaces. Possible mounting areas may include front or side of dash, center console, etc. Location will depend on operator preference and mounting clearance with other vehicle controls. Once the control is properly mounted, it can be easily removed and stored.


Installation should be done at temperatures above 60°F (15.6°C).

1. Select the area of the cab where control will be mounted.
2. Clean installation area and surface of control with isopropyl alcohol or mineral spirits. Allow surface to dry for 15 minutes.
3. Determine length of dual locking strip required. **Do not obstruct the ON/OFF switch.**

For flat surfaces: Use full length locking strips mounted along the length of the control. Strips may be placed on the back of the side of the control.



For curved surfaces: Cut the locking strips to 2 inches. These strips must be placed parallel to the curved surface.



4. Once the selected surfaces are prepared, remove the adhesive back protection strip and press the locking strips into place. Apply pressure across entire surface to work out any trapped air bubbles.
5. Allow the locking strip adhesive to set for 24 hours before mounting the control to the cab surface.

The control can be easily removed by applying a sideways lifting motion to the control. Do not apply excessive force. If the control does not release, gently pry up in the opening under the control with a screwdriver or other flat object.

The PRO-GRIP locking strips can be removed from control and mounting location if no longer needed. Adhesive residue can be cleaned up with mineral spirits.

Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. Western Products offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, L.L.C: MVP®, MVP PLUS™, WESTERN®, WIDE-OUT™.

Printed in U.S.A.